

Garant
PCD slot drill with internal cooling straight cut, PCD, Ø h10 DC: 8 mm

Order data

Order number	209610 8
GTIN	4045197478047
Item class	11Y

Description
Version:

High performance PCD slot drill for the **highest demands in respect to material removal rates** when machining **GRP, CRP** and **graphite**.

Axial angle 0°.

Straight flutes for a neutral cut.

Through-coolant: yes

Tolerance nominal Ø: h10

No. of teeth Z: 2

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA with h6

No. of teeth Z: 2

Flute length L_c : 20 mm

Overhang length L_1 incl. recess: 30 mm

Recess Ø D_1 : 7.4 mm

Overall length L: 80 mm

Shank Ø D_s : 8 mm

Technical description

No. of teeth Z	2
Cutting edge Ø D_c	8 mm
Feed f_z for slot milling in graphite	0.11 mm
Feed f_z for slot milling in GRP CRP	0.04 mm
Recess Ø D_1	7.4 mm
Overhang length L_1 incl. recess	30 mm

Corner chamfer width at 45°	0.1 mm
Shank $\varnothing D_s$	8 mm
Overall length L	80 mm
Flute length L_c	20 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA with h6
Tolerance nominal \varnothing	h10
Corner chamfer angle	45 degrees
Coating	PCD
Tool material	PCD
Standard	Manufacturer's standard
Cutting width a_e for milling operation	Full slot cutting depth 1xD
Through-coolant	yes
Colour ring	black
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------