

**Garant**
**PCD torus cutter with internal cooling straight cut, PCD, Ø e8 DC / R1: 10/1,0 mm**

**Order data**

Order number	209635 10/1,0
GTIN	4045197513458
Item class	11Y

**Description**
**Version:**

**High performance PCD slot drill** for the **highest demands in respect to material removal rates** when machining **GRP, CRP** and **graphite**.

**Straight flutes** for a neutral cut.

Tolerance for corner radius  $R_1 = \pm 0.01$  mm.

No. of teeth Z: 2

Shank: DIN 6535 HA to h6

No. of teeth Z: 2

Flute length  $L_c$ : 8 mm

Corner radius  $R_1$ : 1 mm

Overhang length  $L_1$  incl. recess: 32 mm

Recess Ø  $D_1$ : 9.2 mm

Overall length L: 72 mm

**Technical description**

Feed $f_z$ for side milling in graphite	0.1 mm
Feed $f_z$ for copy milling in GRP CRP	0.09 mm
Feed $f_z$ for copy milling in graphite	0.14 mm
Feed $f_z$ for side milling in GRP CRP	0.06 mm
Corner radius $R_1$	1 mm
Cutting edge Ø $D_c$	10 mm
No. of teeth Z	2

Recess $\varnothing D_1$	9.2 mm
Overhang length $L_1$ incl. recess	32 mm
Shank $\varnothing D_s$	10 mm
Flute length $L_c$	8 mm
Overall length $L$	72 mm
Shank	DIN 6535 HA to h6
Coating	PCD
Tool material	PCD
Standard	Manufacturer's standard
Tolerance nominal $\varnothing$	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.2×D for side milling
Through-coolant	yes
Shank tolerance	h6
Colour ring	black
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------