

Garant
Solid carbide micro slot drill, Diamond, Ø DC × L1: 0,5X15 mm

Order data

Order number	209700 0,5X15
GTIN	4062406187118
Item class	11Y

Description
Version:

With **crystalline diamond sp³ coating**. For the **highest demands regarding performance and precision** in fibre-reinforced composites, CRP, GRP, and graphite. **Extremely tight tolerances** ensure maximum accuracy. Double relief ground with 2 hollow-ground chamfers. **Recess angle $\alpha = 16^\circ$** .

Tolerances:

- **Neck Ø: $D_1 = 0 / -0.01$ mm.**

Note:

At greater tool overhang lengths, use a reduced value for a_p !

Values for:

slots milled from solid: $a_p = 0.1 \times D \times a_{p\text{ korr}}$

side milling: $a_p = 0.2 \times D \times a_{p\text{ korr}}$

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!

e.g: $vf = 18000$ [rpm] × fz [mm/Z] × z

Through-coolant: no

No. of teeth Z : 2

Helix angle: 25 degrees

Shank: DIN 6535 HA to h5

No. of teeth Z : 2

Flute length L_c : 0.7 mm

Overhang length L_1 incl. recess: 15 mm

Overall length L : 50 mm

Shank Ø D_s : 4 mm

Technical description

Flute length L_c	0.7 mm
Overall length L	50 mm
Shank $\varnothing D_s$	4 mm
Overhang length L_1 incl. recess	15 mm
Shank	DIN 6535 HA to h5
Helix angle	25 degrees
No. of teeth Z	2
Cutting edge $\varnothing D_c$	0.2 mm
Corner chamfer angle	90 degrees
Coating	Diamond
Tool material	Solid carbide
Standard	Manufacturer's standard
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Colour ring	black
Type of product	End mill