

Garant
Solid carbide torus cutter, Diamond, Ø e8 DC / R1: 10/1,0 mm

Order data

| | |
|--------------|---------------|
| Order number | 209758 10/1,0 |
| GTIN | 4045197475589 |
| Item class | 11Y |

Description
Version:

With the latest generation of **crystalline diamond coating sp³**, for process reliability in machining **fibre-reinforced composites, CRP, GRP and graphite**. Double relief ground side clearance angle.

Tolerance: Corner radius $R_1 = \pm 0.01$ mm.

No. of teeth Z: 4

Helix angle: 30 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 11 mm

Corner radius R_1 : 1 mm

Overhang length L_1 incl. recess: 60 mm

Recess Ø D_1 : 9.2 mm

Overall length L: 100 mm

Technical description

| | |
|---|----------|
| Recess Ø D_1 | 9.2 mm |
| Corner radius R_1 | 1 mm |
| Feed f_z for copy milling in graphite | 0.091 mm |
| No. of teeth Z | 4 |
| Cutting edge Ø D_c | 10 mm |
| Overhang length L_1 incl. recess | 60 mm |
| Feed f_z for side milling in graphite | 0.091 mm |

| | |
|---|----------------------------------|
| Shank $\varnothing D_s$ | 10 mm |
| Flute length L_c | 11 mm |
| Overall length L | 100 mm |
| Shank | DIN 6535 HA to h6 |
| Helix angle | 30 degrees |
| Coating | Diamond |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Tolerance nominal \varnothing | e8 |
| Spacing of the cutters | unequal spacing |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | 0.2×D for side milling |
| Cutting width a_e for milling operation | 0.05×D for copy milling |
| Through-coolant | no |
| Shank tolerance | h6 |
| Colour ring | black |
| Type of product | End mill |

Services

| | |
|------------------------|-----------|
| Shank grinding Type HB | 129100 HB |
|------------------------|-----------|