

Garant
Solid carbide copy slot drill, Diamond, Ø DC × L1: 0,6X11 mm

Order data

| | |
|--------------|---------------|
| Order number | 209791 0,6X11 |
| GTIN | 4062406188443 |
| Item class | 11Y |

Description
Version:

With **crystalline diamond sp³ coating**. For the **highest demands regarding performance and precision** in fibre-reinforced composites, CRP, GRP, and graphite. **Extremely tight tolerances** ensure maximum accuracy. Double relief ground with 2 hollow-ground chamfers. **Recess angle $\alpha = 16^\circ$** .

Tolerances:

- **Corner radius: Radius contour 0 / -0.005 mm.**
- **Neck Ø: $D_1 = 0 / -0.01$ mm.**

Note:

At greater tool overhang lengths, use a reduced value for a_p !
values for:

copying: $a_p = 0.15 \times D \times a_{p, \text{korr}}$

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!

e.g: $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$

No. of teeth Z: 2

Helix angle: 25 degrees

No. of teeth Z: 2

Flute length L_c : 0.48 mm

Overhang length L_1 incl. recess: 11 mm

Recess Ø D_1 : 0.57 mm

Overall length L: 50 mm

Shank Ø D_s : 4 mm

Technical description

| | |
|----------------|---------|
| Recess Ø D_1 | 0.57 mm |
|----------------|---------|

| | |
|--|----------------------------------|
| Helix angle | 25 degrees |
| Overall length L | 50 mm |
| Flute length L _c | 0.48 mm |
| Cutting edge Ø D _c | 0.6 mm |
| Shank Ø D _s | 4 mm |
| Overhang length L ₁ incl. recess | 11 mm |
| No. of teeth Z | 2 |
| Radius R | 0.3 mm |
| Coating | Diamond |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Tolerance nominal Ø | 0 / -0.005 |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a _e for milling operation | 0.05×D for copy milling |
| Shank | DIN 6535 HA to h5 |
| Through-coolant | no |
| Colour ring | black |
| Type of product | End mill |