

Garant
Solid carbide copy slot drill, Diamond, Ø DC × L1: 1,2X14 mm

Order data

Order number	209791 1,2X14
GTIN	4062406188474
Item class	11Y

Description
Version:

With **crystalline diamond sp³ coating**. For the **highest demands regarding performance and precision** in fibre-reinforced composites, CRP, GRP, and graphite. **Extremely tight tolerances** ensure maximum accuracy. Double relief ground with 2 hollow-ground chamfers. **Recess angle $\alpha = 16^\circ$** .

Tolerances:

- **Corner radius: Radius contour 0 / -0.005 mm.**
- **Neck Ø: $D_1 = 0 / -0.01$ mm.**

Note:

At greater tool overhang lengths, use a reduced value for a_p !
values for:

copying: $a_p = 0.15 \times D \times a_{p, \text{korr}}$

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!

e.g: $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length L_c : 0.96 mm

Overhang length L_1 incl. recess: 14 mm

Recess Ø D_1 : 1.16 mm

Overall length L: 50 mm

Shank Ø D_s : 4 mm

Technical description

Overall length L	50 mm
------------------	-------

Shank $\varnothing D_s$	4 mm
Flute length L_c	0.96 mm
Cutting edge $\varnothing D_c$	1.2 mm
No. of teeth Z	2
Overhang length L_1 incl. recess	14 mm
Recess $\varnothing D_1$	1.16 mm
Helix angle	30 degrees
Radius R	0.6 mm
Coating	Diamond
Tool material	Solid carbide
Standard	Manufacturer's standard
Tolerance nominal \varnothing	0 / -0.005
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	black
Type of product	End mill