

Garant
PickPocket end milling head, HB730, Ø D h10: 16 mm

Order data

Order number	210050 16
GTIN	4045197891259
Item class	21M

Description
Note:

Standard application values for $a_{p,max} \leq 0.5 \times D$.

Head length l: 20 mm

Flute length L_2 : 12 mm

Feed f_z for slot milling in steel < 900 N/mm²: 0.08 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.1 mm

Technical description

Feed f_z for slot milling in steel < 900 N/mm ²	0.08 mm
Flute length L_2	12 mm
Cutter Ø D	16 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.1 mm
Head length l	20 mm
Arbor size	16 mm
Corner rounding r_v	0.32
Series	GARANT Master Steel
Series	TopCut
Grade	HB730

Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Number of cutting edges Z	3
Spacing of the cutters	unequal spacing
Helix angle	38 degrees
Helix angle characteristic	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.3×D for side milling mm
Cutting width a_e for milling operation	Full slot cutting depth 1×D mm
Machining strategy	HPC
Through-coolant	no
suitable arbor	GARANT TopCut
Type of product	Cutter insert for milling