

Garant
End milling head, 45° chamfer with IC, HB730, Ø D h10: 20 mm

Order data

Order number	210100 20
GTIN	4045197557414
Item class	21M

Description
Note:

Standard application values for $a_{p\max} \leq 0.5 \times D$.

Head length l: 25 mm

Flute length L_2 : 15 mm

Corner chamfer width at 45°: 0.4 mm

Feed f_z for slot milling in steel < 900 N/mm²: 0.08 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.1 mm

Technical description

Cutter Ø D	20 mm
Flute length L_2	15 mm
Head length l	25 mm
Corner chamfer width at 45°	0.4 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.1 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.08 mm
Arbor size	20 mm
Corner chamfer angle	45 degrees
Series	TopCut

Grade	HB730
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Number of cutting edges Z	3
Spacing of the cutters	unequal spacing
Helix angle	40 degrees
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.3×D for side milling mm
Cutting width a_e for milling operation	Full slot cutting depth 1×D mm
Machining strategy	HPC
Through-coolant	yes
suitable arbor	GARANT TopCut
Type of product	Cutter insert for milling

Accessories

Plug-in adapter for torque wrench Type 16X5	219986 16X5
Assembly wrench Type 16X5	219987 16X5