

**Garant**
**End milling head, 45° chamfer, HB730, Ø D h10: 20 mm**

**Order data**

Order number	210200 20
GTIN	4045197523044
Item class	21M

**Description**
**Note:**

Standard application values for  $a_{p,max} \leq 0.5 \times D$ .

Head length l: 25 mm

Flute length  $L_2$ : 15 mm

Corner chamfer width at 45°: 0.4 mm

Feed  $f_z$  for slot milling in steel < 900 N/mm<sup>2</sup>: 0.07 mm

Feed  $f_z$  for side milling in steel < 900 N/mm<sup>2</sup>: 0.09 mm

**Technical description**

Head length l	25 mm
Flute length $L_2$	15 mm
Cutter Ø D	20 mm
Corner chamfer width at 45°	0.4 mm
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.09 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.07 mm
Arbor size	20 mm
Corner chamfer angle	45 degrees
Series	TopCut
Grade	HB730

Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Number of cutting edges Z	4
Helix angle	40 degrees
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.3×D for side milling mm
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D mm
Through-coolant	no
suitable arbor	GARANT TopCut
Type of product	Cutter insert for milling

## Accessories

Assembly wrench Type 16X5	219987 16X5
Plug-in adapter for torque wrench Type 16X5	219986 16X5