

**Garant**
**Torus milling head HPC, HB7820, Ø D h10 / R: 25/2 mm**

**Order data**

Order number	210255 25/2
GTIN	4045197607560
Item class	21M

**Description**
**Note:**

Standard application values for slots milled from solid at  $a_{p\ max} \leq 0.5 \times D$ .

Head length  $l$ : 32 mm

Flute length  $L_2$ : 19 mm

Corner radius: 2 mm

Feed  $f_z$  for slot milling in short-chipping aluminium: 0.22 mm

Feed  $f_z$  for side milling in short-chipping aluminium: 0.28 mm

**Technical description**

Head length $l$	32 mm
Flute length $L_2$	19 mm
Milling head Ø D	25 mm
Feed $f_z$ for side milling in short-chipping aluminium	0.28 mm
Feed $f_z$ for slot milling in short-chipping aluminium	0.22 mm
Corner radius	2 mm
Arbor size	24 mm
Grade	HB7820
Tool material	Solid carbide
Standard	Manufacturer's standard

Type	W
Number of cutting edges Z	3
Helix angle	42 degrees
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Machining strategy	HPC
Through-coolant	yes
Type of product	Cutter insert for milling