

Garant
Roughing / finishing milling head, 45° chamfer, HB730, Ø D h10: 25 mm

Order data

Order number	210280 25
GTIN	4045197543127
Item class	21M

Description
Note:

Standard application values for $a_{p\max} \leq 0.5 \times D$.

Head length l: 45 mm

Flute length L_2 : 32 mm

Corner chamfer width at 45°: 0.5 mm

Feed f_z for slot milling in steel < 900 N/mm²: 0.1 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.1 mm

Technical description

Flute length L_2	32 mm
Head length l	45 mm
Cutter Ø D	25 mm
Corner chamfer width at 45°	0.5 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.1 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.1 mm
Arbor size	24 mm
Corner chamfer angle	45 degrees
Series	TopCut
Grade	HB730

Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Milling profile	NF
Number of cutting edges Z	4
Helix angle	45 degrees
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.3×D for side milling mm
Cutting width a_e for milling operation	Full slot cutting depth 1×D mm
Machining strategy	HPC
Through-coolant	no
suitable arbor	GARANT TopCut
Type of product	Cutter insert for milling

Accessories

Plug-in adapter for torque wrench Type 21X5	219986 21X5
Assembly wrench Type 21X5	219987 21X5