

Garant
**GARANT Master Steel SlotMachine solid carbide roughing milling head,
HB730, Ø D d11: 16 mm**

Order data

Order number	210290 16
GTIN	4045197891457
Item class	21M

Description
Note:

Standard application values for $a_{p\max} \leq 0.75 \times D$.

Head length l: 28 mm

Flute length L_2 : 20 mm

Corner chamfer width at 45°: 0.8 mm

Feed f_z for slot milling in steel < 900 N/mm²: 0.07 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.1 mm

Technical description

Feed f_z for side milling in steel < 900 N/mm ²	0.1 mm
Corner chamfer width at 45°	0.8 mm
Head length l	28 mm
Cutter Ø D	16 mm
Flute length L_2	20 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.07 mm
Arbor size	16 mm
Corner chamfer angle	45 degrees
Series	GARANT Master Steel

Series	TopCut
Grade	HB730
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Milling profile	NR
Number of cutting edges Z	5
Helix angle	42 degrees
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.3×D for side milling mm
Cutting width a_e for milling operation	Full slot cutting depth 1×D mm
Through-coolant	no
suitable arbor	GARANT TopCut
Type of product	Cutter insert for milling