

Garant
TPC milling head with chip separators 3×D, HB730, Ø D f8: 10 mm

Order data

Order number	210344 10
GTIN	4045197722331
Item class	21M

Description
Version:
Milling head specially designed for TPC applications.
Note:
 h_{\max} : The values stated in the table are maximum values.

Cutting data for conventional milling can be found in the machining handbook No. 110020.

 $a_{e \max} = 0.08 \times D$ for TPC machining.

Head length l : 35.5 mm

Flute length L_2 : 30 mm

Corner chamfer width at 45°: 0.2 mm

Average chip thickness h_{\max} for TPC milling in steel < 900 N/mm²: 0.045 mm

Technical description

Cutter Ø D	10 mm
Flute length L_2	30 mm
Head length l	35.5 mm
Average chip thickness h_{\max} for TPC milling in steel < 900 N/mm ²	0.045 mm
Corner chamfer width at 45°	0.2 mm
Arbor size	10 mm
Corner chamfer angle	45 degrees
Series	TopCut

Grade	HB730
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Number of cutting edges Z	5
Helix angle	45 degrees
Helix angle characteristic	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0,08xD mm
Machining strategy	TPC
Through-coolant	no
suitable arbor	GARANT TopCut
Type of product	Cutter insert for milling