

**Garant**
**Copy milling head, hard machining, HB7730, Ø D h10: 16 mm**

**Order data**

Order number	210370 16
GTIN	4045197523488
Item class	21M

**Description**

Copy milling head, hard machining 16 mm Head length l: 20 mm

Flute length  $L_2$ : 12 mm

maximum cutting depth  $a_{p,max}$  in steel < 60 HRC: 0.5 mm

Feed  $f_z$  for copy milling in steel < 60 HRC: 0.06 mm

**Technical description**

Flute length $L_2$	12 mm
Head length l	20 mm
Cutter Ø D	16 mm
maximum cutting depth $a_{p,max}$ in steel < 60 HRC	0.5 mm
Arbor size	16 mm
Feed $f_z$ for copy milling in steel < 60 HRC	0.06 mm
Series	TopCut
Grade	HB7730
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Number of cutting edges Z	4

Helix angle	15 degrees
Direction of infeed	horizontal and oblique
Cutting width $a_e$ for milling operation	0.5×D for side milling
Through-coolant	no
suitable arbor	GARANT TopCut
Type of product	Cutter insert for milling

---

## Accessories

Plug-in adapter for torque wrench Type 13X4	219986 13X4
Assembly wrench Type 13X4	219987 13X4