

**Garant**
**Milling head for front and back chamfering, 90°, HB730, Ø D ± 0.01: 16 mm**

**Order data**

Order number	210380 16
GTIN	4045197527400
Item class	21M

**Description**
**Note:**

$$a_{e\max} = a_{p\max}$$

Direction of infeed: horizontal

Arbor size: 12 mm

Head length l: 16 mm

Flute length  $L_2$ : 2 mm

maximum cutting depth  $a_{p\max}$  in steel < 900 N/mm<sup>2</sup>: 1.8 mm

Feed  $f_z$  in steel < 900 N/mm<sup>2</sup>: 0.1 mm

Suitable chuck key No. 219987; No. 219986: 10×4

**Technical description**

Head length l	16 mm
Flute length $L_2$	2 mm
Suitable chuck key No. 219987; No. 219986	10×4
Cutter Ø D	16 mm
maximum cutting depth $a_{p\max}$ in steel < 900 N/mm <sup>2</sup>	1.8 mm
Corner chamfer angle	45 degrees
Arbor size	12 mm
Feed $f_z$ in steel < 900 N/mm <sup>2</sup>	0.1 mm

Series	TopCut
Grade	HB730
Tool material	Solid carbide
Countersink tip angle	90
Standard	Manufacturer's standard
Type	N
Number of cutting edges Z	6
Direction of infeed	horizontal
Through-coolant	no
Type of product	Cutter insert for milling

---

## Accessories

Assembly wrench Type 10X4	219987 10X4
Plug-in adapter for torque wrench Type 10X4	219986 10X4