

## Garant

### Parallel arbor, with through-coolant, Weldon shank, for cutter head Ø D: 10 mm



#### Order data

Order number	210557 10
GTIN	4045197557735
Item class	21Z

#### Description

##### Version:

Precision-ground arbor for GARANT TopCut screw-in heads.

**System radial run-out ≤ 10 µm** due to the combination of taper and flat face.

##### Note:

**Maximum milled depth** =  $L_1 + l$ ;  $l$  = see dimensions of the screw-in heads: No. 210050 – 210410.

Assembly wrench = No. 219987.

Plug-in adapter for torque wrench = No. 219986.

For long tool overhang, reduce technology data.

Through-coolant: yes

External Ø  $d_1$ : 9.8 mm

Overall length  $L_{tot}$ : 75 mm

Reach  $L_1$ : 24 mm

Shank Ø  $D_s$ : 16 mm

recommended tightening torque: 5 Nm

#### Technical description

Reach $L_1$	24 mm
for cutter head Ø D	10 mm
External Ø $d_1$	9.8 mm
Shank Ø $D_s$	16 mm
Overall length $L_{tot}$	75 mm

recommended tightening torque	5 Nm
Series	TopCut
Adapter	Weldon shank
Through-coolant	yes
Type of product	Threaded copy mill arbor