

## Garant

### Solid carbide tapered arbor long, Plain shank, for cutter head Ø D: 20 mm



#### Order data

Order number	210570 20
GTIN	4045197522795
Item class	21Z

#### Description

##### Version:

Precision-ground arbor for GARANT TopCut screw-in heads.

**System radial run-out  $\leq 10 \mu\text{m}$**  due to the combination of taper and flat face.

With plain shank (for HSC machining). **Tolerance = h6.**

##### Note:

**Maximum milled depth** =  $L_1 + l$ ;  $l$  = see dimensions of the screw-in heads: No. 210050 – 210410.

Assembly wrench = No. 219987.

Plug-in adapter for torque wrench = No. 219986.

For long tool overhang, reduce technology data.

Through-coolant: yes

External  $\varnothing d_1$ : 19.8 mm

Overall length  $L_{\text{tot}}$ : 190 mm

Reach  $L_1$ : 132 mm

Shank  $\varnothing D_s$  h6: 25 mm

recommended tightening torque: 25 Nm

#### Technical description

Reach $L_1$	132 mm
Shank $\varnothing D_s$ h6	25 mm
External $\varnothing d_1$	19.8 mm
for cutter head $\varnothing D$	20 mm
Overall length $L_{\text{tot}}$	190 mm
recommended tightening torque	25 Nm

Series	TopCut
Adapter	Plain shank
Through-coolant	yes
Type of product	Threaded copy mill arbor