

Garant
Torque screwdriver, fixed setting, set torque: 5,7 Nm

Order data

Order number	211750 5,7
GTIN	4045197553232
Item class	21B

Description
Version:

Torque screwdriver with easy-grip 2-component T-handle. The torque is fixed. Toolholder with permanent magnet.

Function:

When the torque is reached the screwdriver triggers **with clearly audible and perceptible signal**. The long-travel indication gives the user an unmistakable signal that the set torque has been reached.

Application:

In conjunction with **1/4 inch bits** with **C 6.3** or **E 6.3 shank**, e.g. **Torx Plus® bit No. 674252**. Ideal for precise tightening of indexable inserts to the specified torque.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

Supplied **without** bit.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 10\%$

Bit socket: D 6,3

Bit socket: F 6.3

Torque measuring accuracy: $\pm 10\%$
 Overall length L: 107 mm
 Blade length: 50 mm
 set torque: 5.7 Nm

Technical description

Blade length	50 mm
Torque measuring accuracy	$\pm 10\%$
set torque	5.7 Nm
Bit socket	D 6,3
Bit socket	F 6.3
Standard	DIN EN ISO 6789
Measurement process	Torque
Feedback	triggering
Connection format	Bit holder 1/4 inch
Adjustable trigger value	non-adjustable
Trigger principle	Mechanical long travel release
Overall length L	107 mm
Reversible reading	Nm
Setting the trigger value	pre-set
Direction of tightening	Right-hand tightening
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque screwdriver

Accessories

"TQ-Station" – storage station for torque screwdrivers	659964
--------------------------------------------------------	--------

