

Garant

Copy mill 0° negative, with bore, Ø D / number of teeth Z: 125/10 mm


Order data

Order number	212145 125/10
GTIN	4045197192837
Item class	210

Description
Version:

Milling body with irregular pitch for smooth cutting.

- **High axial run-out accuracy and concentricity**
- **Stepless repositioning as the cutting edge wears.**

Attention:

Retaining screws and retaining washers should **not** be used for inserts with positive geometry.

Note:

Use GARANT torque screwdriver TQ No. **211750 size 3.8** with bit No. **674252 size 15IP**.

$a_{p\ max} = 4.0\ mm$.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 10

Ø D₃: 113 mm

Overall length L_{tot}: 63 mm

Mounting bore Ø: 40 mm

Circular interpolation milling Ø D_{min}: 238 mm

Circular interpolation milling Ø D_{max}: 248 mm

Technical description

Overall length L_{tot}	63 mm
$\varnothing D_3$	113 mm
Mounting bore \varnothing	40 mm
Set of retaining screws	219807 (15IP; 3.8 Nm)
Cutting edge $\varnothing D_c$	125 mm
suitable indexable insert	RD..12T3
Pack of insert screws	219805 (15IP; 3.8 Nm)
Number of cutting edges Z	10
Through-coolant	yes
Circular interpolation milling $\varnothing D_{min}$	238 mm
Circular interpolation milling $\varnothing D_{max}$	248 mm
Circular interpolation milling a_p	4 mm
Ramping length L for α_{max}	109.94 mm
Ramping angle α_{max}	0.44 degrees
Shank type	with bore
Milling head suitable for insert shape	round
Milling application	Ramping
Milling application	Circular milling
Spacing of the cutters	unequal spacing
Tool exchange	PowerCard

Accessories

Set of insert screws 10-piece	219807
Torque screwdriver, fixed setting set torque 3,8 Nm	211750 3,8
Set of insert screws 10-piece	219805
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP	674252 15IP