

## Solid carbide copy milling cutter extra long, Plain shank, Ø D: 16 mm



### **Order data**

Order number	212592 16
GTIN	4045197761477
Item class	210

## **Description**

#### **Version:**

Exactly accurate insert bedding due to optimised design of insert and insert seat tolerances. Highest interchange accuracy guaranteed:  $\pm$  0.015 mm.

#### **Application:**

General use for finishing and semi-finishing operations.

**Solid carbide** – for large depths of cut and to minimise vibration.

#### Note:

Calculate the speed based on the effective  $\emptyset$  D<sub>w</sub>. Use GARANT torque screwdriver TQ No.

211750 size 3.0 with bit No. 674252 size 15IP.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 2

Overhang L<sub>1</sub>: 55 mm

Overall length Ltot: 175 mm

Ø d₁: 14 mm

Shank Ø D, h6: 16 mm

Insert screw: 219873 (15IP; 3.0 Nm)

## **Technical description**

Number of cutting edges Z	2
Shank Ø D₅ h6	16 mm
Overhang L <sub>1</sub>	55 mm
$\emptyset$ d <sub>1</sub>	14 mm
Cutting edge Ø D <sub>C</sub>	16 mm

Overall length L <sub>tot</sub>	175 mm
Insert screw	219873 (15IP; 3.0 Nm)
Through-coolant	yes
Shank type	Plain shank
Milling application	Copy milling
Tool exchange	PowerCard

# **Accessories**

Clamping screw	219872
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP	674252 15IP
Torque screwdriver, fixed setting set torque 3,0 Nm	211750 3,0