

Copy mill long, Plain shank, Ø D: 20 mm



Order data

Order number	212603 20
GTIN	4045197712721
Item class	210

Description

Version:

Exactly accurate insert bedding due to optimised design of insert and insert seat tolerances. Highest interchange accuracy guaranteed: \pm 0.015 mm.

Application:

General use for finishing and semi-finishing operations.

Steel – for general use in machining drop-forgings, and in tool and mould making.

Note:

Calculate the speed based on the effective \emptyset D_w. Use GARANT torque screwdriver TQ No.

211750 size 5.0 with bit No. 674252 size 20IP.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 2

Overhang L_1 : 34 mm Length \emptyset d_1 : 75 mm

Overall length Ltot: 141 mm

Ø d₁: 17 mm

Shank Ø D, h6: 20 mm

Technical description

Length Ø d₁	75 mm
$\emptyset d_1$	17 mm
Overall length L _{tot}	141 mm
Overhang L ₁	34 mm

Shank Ø D _s h6	20 mm
Cutting edge Ø D _c	20 mm
Insert screw	219874 (20IP; 5.0 Nm)
Number of cutting edges Z	2
Through-coolant	yes
Shank type	Plain shank
Milling application	Copy milling
Tool exchange	PowerCard

Accessories

Torque screwdriver, fixed setting set torque 5,0 Nm	211750 5,0
Clamping screw	219874
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 20IP	674252 20IP