

Garant

**FeedKing high feed rate indexable face mill, with bore, \varnothing D / number of teeth
Z: 50/7 mm**



Order data

Order number	212910 50/7
GTIN	4045197554499
Item class	210

Description

Version:

Dynamic cutting edge geometry for highest feed rates. Extremely smooth cutting due to **self-stabilising insert bedding**. **Optimised geometry** for reduced cutting forces, thereby reducing the stress on the main spindle.

Advantage:

Particularly cost-effective due to **exceptionally sturdy 4-edge** inserts.

Note:

Use GARANT torque screwdriver TQ No. **211750 size 2.2** with bit No. **674252 size 9IP**.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 7

\varnothing D₃: 36.7 mm

maximum cutting depth $a_{p,max}$: 0.85 mm

Overall length L_{tot} : 40 mm

Mounting bore \varnothing : 22 mm

Circular interpolation milling \varnothing D_{min}: 89.5 mm

Technical description

Ø D ₃	36.7 mm
Cutting edge Ø D _c	50 mm
Pack of insert screws	219810 (9IP; 2.2 Nm)
Overall length L _{tot}	40 mm
suitable indexable insert	XD.. 070308
maximum cutting depth a _{p max}	0.85 mm
Mounting bore Ø	22 mm
Number of cutting edges Z	7
Through-coolant	yes
Circular interpolation milling Ø D _{min}	89.5 mm
Circular interpolation milling Ø D _{max}	98.9 mm
Circular interpolation milling a _p	0.85 mm
Ramping length L for α _{max}	57 mm
Ramping angle α _{max}	0.9 degrees
Setting angle κ	10 degrees
Shank type	with bore
Milling application	Circular milling
Milling application	Ramping
Milling application	Plunging
Spacing of the cutters	unequal spacing
Machining strategy	HPC
Tool exchange	PowerCard

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 9IP	674252 9IP
Set of insert screws pack of 10 10-piece	219810
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2

