

Garant

**Hi5 high feed rate indexable face mill, with thread, Ø D / number of teeth Z:
40/4 mm**


Order data

Order number	213205 40/4
GTIN	4045197783530
Item class	210

Description
Version:

Particularly smooth-running, due to unequal spacing of the teeth.

Note:

Use GARANT torque screwdriver TQ No. **211750 size 2.2** with bit No. **674252 size 10IP**.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 4

Ø D₁ h6: 17 mm

Ø D₂: 29 mm

Ø D₃: 25.6 mm

maximum cutting depth a_{p max}: 1.4 mm

Overall length L_{tot}: 43 mm

Technical description

Through-coolant	yes
Number of cutting edges Z	4
Ø D ₂	29 mm
maximum cutting depth a _{p max}	1.4 mm
Ø D ₃	25.6 mm

suitable indexable insert	POMX 0704..
Overall length L_{tot}	43 mm
Cutting edge $\varnothing D_c$	40 mm
Pack of insert screws	219884 (10IP; 2.2 Nm)
Mounting thread M	M16
$\varnothing D_1$ h6	17 mm
Shank type	with thread
Spacing of the cutters	unequal spacing
Tool exchange	PowerCard

Accessories

Set of insert screws 10 pieces	219884
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 10IP	674252 10IP