

Garant

**Hi5 high feed rate indexable face mill, with bore, Ø D / number of teeth Z:
40/4 mm**



Order data

Order number	213210 40/4
GTIN	4045197783547
Item class	210

Description

Version:

Particularly smooth-running, due to unequal spacing of the teeth.

Note:

Use GARANT torque screwdriver TQ No. **211750 size 2.2** with bit No. **674252 size 10IP**.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 4

Ø D₃: 25.6 mm

maximum cutting depth a_{p,max}: 1.4 mm

Overall length L_{tot}: 40 mm

Mounting bore Ø: 16 mm

suitable indexable insert: POMX 0704..

Technical description

Ø D ₃	25.6 mm
Overall length L _{tot}	40 mm
suitable indexable insert	POMX 0704..

maximum cutting depth $a_{p\max}$	1.4 mm
Pack of insert screws	219884 (10IP; 2.2 Nm)
Number of cutting edges Z	4
Mounting bore \varnothing	16 mm
Cutting edge $\varnothing D_c$	40 mm
Through-coolant	yes
Setting angle κ	90 degrees
Shank type	with bore
Spacing of the cutters	unequal spacing
Tool exchange	PowerCard

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 10IP	674252 10IP
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
Set of insert screws 10 pieces	219884