

Garant

**Hi5 high feed rate indexable face mill, with bore, Ø D / number of teeth Z:
63/6 mm**


Order data

Order number	213210 63/6
GTIN	4045197783578
Item class	210

Description
Version:

Particularly smooth-running, due to unequal spacing of the teeth.

Note:

Use GARANT torque screwdriver TQ No. **211750 size 2.2** with bit No. **674252 size 10IP**.

Tool exchange: PowerCard

Through-coolant: yes

Number of cutting edges Z: 6

Ø D₃: 48.6 mm

maximum cutting depth a_{p,max}: 1.4 mm

Overall length L_{tot}: 50 mm

Mounting bore Ø: 27 mm

suitable indexable insert: POMX 0704..

Technical description

Overall length L _{tot}	50 mm
Pack of insert screws	219884 (10IP; 2.2 Nm)

Ø D ₃	48.6 mm
Number of cutting edges Z	6
Mounting bore Ø	27 mm
suitable indexable insert	POMX 0704..
Cutting edge Ø D _c	63 mm
maximum cutting depth a _{p max}	1.4 mm
Through-coolant	yes
Setting angle κ	90 degrees
Shank type	with bore
Spacing of the cutters	unequal spacing
Tool exchange	PowerCard

Accessories

Set of insert screws 10 pieces	219884
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 10IP	674252 10IP