

## Softcut® HSI, with threaded shank, Ø D / number of teeth Z: 32/2 mm



#### Order data

Order number	214853 32/2
GTIN	4045197608680
Item class	210

## **Description**

#### **Version:**

Individual tool geometry ensures very smooth cutting. Exceptionally sturdy insert design for best feed rates. Indexable inserts are secured by special screws with high shear resistance.

#### **Application:**

For outstanding surface quality. Burr-free milling.

#### Note:

Use GARANT torque screwdriver TQ No. 211750 size 3.0 with bit No. 674252 size 15IP.

### For exact 90° corners, select $a_p = 8$ mm.

To use all 4 cutting edges, the insert must always be turned in the direction shown (anticlockwise).

Tool exchange: PowerCard

maximum cutting depth a<sub>p max</sub>: 10 mm

Overall length Ltot: 42 mm

Ø D<sub>1</sub> h6: 17 mm Ø D<sub>2</sub>: 28.7 mm

Mounting thread M: M16

suitable indexable insert: SO., 1205.,

## **Technical description**

suitable indexable insert	SO 1205
maximum cutting depth a <sub>p max</sub>	10 mm

$\emptyset$ D <sub>1</sub> h6	17 mm
Pack of insert screws	219833 (15IP; 3.0 Nm)
$\emptyset$ D <sub>2</sub>	28.7 mm
Overall length L <sub>tot</sub>	42 mm
Cutting edge Ø D <sub>c</sub>	32 mm
Mounting thread M	M16
Number of cutting edges Z	2
Shank type	with threaded shank
Setting angle κ	90 degrees
Milling application	End milling
Spacing of the cutters	unequal spacing
Through-coolant	yes
Tool exchange	PowerCard
Type of product	Indexable insert cutter

# **Accessories**

Torque screwdriver, fixed setting set torque 3,0 Nm	211750 3,0
Set of insert screws 10 pieces	219833
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 5IP	674252 5IP