

## Softcut® HSI, close pitch, with bore, Ø D / number of teeth Z: 100/10 mm



#### **Order data**

Order number	214908 100/10
GTIN	4045197674692
Item class	210

## **Description**

#### **Version:**

Wear-resistant heat-treated steel with corrosion-inhibiting coating. Precise indexable insert seating by use of appropriate torque. Wide and close tooth pitches for individual milling strategies.

#### **Application:**

Particularly suitable for machines with lower drive power and for machining at greater depths and small entry diameters.

#### Note:

To use all 4 cutting edges, the insert must always be turned in the direction shown (anticlockwise).

Use GARANT torque screwdriver TQ No. 211750 size 2.2 with bit No. 674252 size 8IP. For exact 90° corners, select  $a_0 = 6$  mm.

Tool exchange: PowerCard

maximum cutting depth ap max: 6 mm

Overall length L<sub>tot</sub>: 50 mm Mounting bore Ø: 32 mm

suitable indexable insert: SO.. 0836.. Pack of insert screws: 219863 (8IP; 2.2 Nm)

# **Technical description**

Mounting bore $\varnothing$	32 mm
Cutting edge $\varnothing$ $D_c$	100 mm
suitable indexable insert	SO 0836
maximum cutting depth a <sub>p max</sub>	6 mm
Overall length L <sub>tot</sub>	50 mm
Pack of insert screws	219863 (8IP; 2.2 Nm)
Number of cutting edges Z	10
Series	Softcut <sup>®</sup>
Shank type	with bore
Setting angle κ	90 degrees
Milling application	Corner milling
Spacing of the cutters	unequal spacing
Through-coolant	yes
Tool exchange	PowerCard
Type of product	Indexable insert cutter

# **Accessories**

Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP	674252 8IP
Set of insert screws 10 pieces	219863