

Indexable face / shoulder mill 90°, Weldon shank, \varnothing D / number of teeth Z: 25/2 mm



Order data

Order number	215045 25/2
GTIN	4045197221674
Item class	210

Description

Version:

Made of hardened special steel for low vibration and long life. Very good surface finishes are obtained due to projecting flat cutting edge.

Note

To use all 4 cutting edges, the insert always has to be turned in the indicated direction.

Use GARANT torque screwdriver TQ No. 211750 size 2.2 with bit No. 674252 size 9IP.

Tool exchange: PowerCard

Overhang L₁: 31 mm

Overall length L_{tot} : 105 mm Shank Ø D_s h6: 25 mm

suitable indexable insert: SOMT 09T304 Pack of insert screws: 219810 (9IP; 2.2 Nm)

Technical description

Overall length L_{tot}	105 mm
Overhang L ₁	31 mm
Pack of insert screws	219810 (9IP; 2.2 Nm)
Shank Ø D₅ h6	25 mm
Cutting edge \emptyset D_c	25 mm
suitable indexable insert	SOMT 09T304

Number of cutting edges Z	2
Shank type	Weldon shank
Setting angle κ	90 degrees
Milling application	End milling
Spacing of the cutters	unequal spacing
Through-coolant	yes
Tool exchange	PowerCard
Type of product	Indexable insert cutter

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 9IP	674252 9IP
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
Set of insert screws pack of 10 10-piece	219810