

Indexable face mill 90°, with bore, Ø D / number of teeth Z: 100/8 mm



Order data

Order number	215055 100/8
GTIN	4045197750341
Item class	220

Description

Version:

Made of hardened special steel for low vibration and long life. Very good surface finishes are obtained due to projecting flat cutting edge.

Attention:

Without a PowerCard!

Note:

To use all 4 cutting edges, the insert always has to be turned in the indicated direction.

Use GARANT torque screwdriver TQ No. 211750 size 2.2 with bit No. 674252 size 9IP.

Through-coolant: yes Overall length L_{tot} : 50 mm Mounting bore \varnothing : 32 mm

suitable indexable insert: SOMT 09T304 Pack of insert screws: 219810 (9IP; 2.2 Nm)

Technical description

Cutting edge \varnothing D _c	100 mm
Pack of insert screws	219810 (9IP; 2.2 Nm)



Overall length L _{tot}	50 mm
suitable indexable insert	SOMT 09T304
Mounting bore Ø	32 mm
Number of cutting edges Z	8
Shank type	with bore
Setting angle κ	90 degrees
Milling application	End milling
Through-coolant	yes
Type of product	Indexable insert cutter

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 9IP	674252 9IP
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
Set of insert screws pack of 10 10-piece	219810