

Indexable face mill 90°, with bore, Ø D / number of teeth Z: 40/4 mm



Order data

Order number	215055 40/4
GTIN	4045197750303
Item class	220

Description

Version:

Made of hardened special steel for low vibration and long life. Very good surface finishes are obtained due to projecting flat cutting edge.

Attention:

Without a PowerCard!

Note:

To use all 4 cutting edges, the insert always has to be turned in the indicated direction.

Use GARANT torque screwdriver TQ No. 211750 size 2.2 with bit No. 674252 size 9IP.

Through-coolant: yes Overall length L_{tot}: 40 mm Mounting bore Ø: 16 mm

suitable indexable insert: SOMT 09T304 Pack of insert screws: 219810 (9IP; 2.2 Nm)

Technical description

suitable indexable insert	SOMT 09T304
Overall length L _{tot}	40 mm
Mounting bore Ø	16 mm



Number of cutting edges Z	4
Pack of insert screws	219810 (9IP; 2.2 Nm)
Cutting edge Ø D _c	40 mm
Shank type	with bore
Setting angle ĸ	90 degrees
Milling application	End milling
Through-coolant	yes
Type of product	Indexable insert cutter

Accessories

Set of insert screws pack of 10 10-piece	219810
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 9IP	674252 9IP
Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2