

HOLEX
Indexable face mill 90°, with bore, Ø D / number of teeth Z: 50/5 mm


Order data

Order number	215055 50/5
GTIN	4045197750310
Item class	220

Description

Version:

Made of hardened special steel for low vibration and long life. Very good surface finishes are obtained due to projecting flat cutting edge.

Attention:

Without a PowerCard!

Note:

To use all **4 cutting edges**, the insert **always has to be turned in the indicated direction**.

Use GARANT torque screwdriver TQ No. **211750 size 2.2** with bit No. **674252 size 9IP**.

Through-coolant: yes

Overall length L_{tot} : 40 mm

Mounting bore Ø: 22 mm

suitable indexable insert: SOMT 09T304

Pack of insert screws: 219810 (9IP; 2.2 Nm)

Technical description

Overall length L_{tot}	40 mm
suitable indexable insert	SOMT 09T304

Cutting edge $\varnothing D_c$	50 mm
Mounting bore \varnothing	22 mm
Number of cutting edges Z	5
Pack of insert screws	219810 (9IP; 2.2 Nm)
Shank type	with bore
Setting angle κ	90 degrees
Milling application	End milling
Through-coolant	yes
Type of product	Indexable insert cutter

Accessories

Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 9IP	674252 9IP
Set of insert screws pack of 10 10-piece	219810