

Garant
Softcut® indexable chamfer mill MTC, with bore, Angle γ : 15 degrees


Order data

Order number	215152 15
GTIN	4045197798886
Item class	210

Description

Version:

Robust plug-in chamfer mill. Insert seat enclosed on several sides for stabilisation of the cutters and to take up the vertical and radial forces.

Application:

For wide chamfers in steel fabrications. Outstandingly suitable for roughing and semi-roughing applications.

Note:

Stepless surfaces are achieved.

Use GARANT torque screwdriver TQ No. **211750 size 3.8** with bit No. **674252 size 15IP**.

Tool exchange: PowerCard

Number of effective inserts Z_{eff} : 3

Number of indexable inserts: 6

Overall length L_{tot} : 50 mm

smallest $\varnothing D$: 35 mm

largest $\varnothing D_1$: 92 mm

achievable chamfer width b : 27.8 mm

Technical description

suitable indexable insert	AP.T 1805..
achievable chamfer length l	29.5 mm
achievable chamfer width b	27.8 mm
smallest \varnothing D	35 mm
Angle γ	15 degrees
Mounting bore \varnothing	27 mm
largest \varnothing D ₁	92 mm
Pack of insert screws	219808 (15IP; 3.8 Nm)
Number of effective inserts Z _{eff}	3
Overall length L _{tot}	50 mm
achievable chamfer height h	7.5 mm
Feed rate per tooth at h _{max}	0.4 mm
Number of indexable inserts	6
Shank type	with bore
Spacing of the cutters	unequal spacing
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard
Type of product	Indexable insert cutter

Accessories

Set of insert screws 10-piece	219808
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP	674252 15IP
Torque screwdriver, fixed setting set torque 3,8 Nm	211750 3,8