

## Softcut® 90° shoulder mill MTC, with bore, Ø D / number of teeth Z: 40/3 mm



#### **Order data**

Order number	215160 40/3
GTIN	4045197349255
Item class	210

### **Description**

#### **Version:**

High precision square shoulder milling cutter with irregular pitch for very smooth cutting, very high precision and cutting power. High performance indexable square shoulder milling cutter with special geometry for reduced cutting forces for MTC applications under unstable conditions or for spindles with low drive power.

#### **Application:**

For corner milling to large depths, also slotting. General use in all steels including stainless steels. Especially for **MTC** (**Multi Task Cutting**) use on the new generation of turning / milling centres (**MTM**).

#### Note:

Use GARANT torque screwdriver TQ No. 211750 size 3.8 with bit No. 674252 size 15IP.

The insert pocket must be modified when using indexable inserts with a radius greater than 3.1 mm.

Overall length L<sub>tot</sub>: 40 mm Mounting bore Ø: 16 mm

Circular interpolation milling  $\varnothing$  D<sub>min</sub>: 61.4 mm Circular interpolation milling  $\varnothing$  D<sub>max</sub>: 78.5 mm

Circular interpolation milling  $a_p$ : 1 mm Ramping angle  $\alpha_{max}$ : 1.8 degrees

# **Technical description**

Mounting bore ∅	
Overall length L <sub>tot</sub>	40 mm
Pack of insert screws	219808 (15IP; 3.8 Nm)
suitable indexable insert	AP 1805
Cutting edge Ø D <sub>c</sub>	40 mm
Number of cutting edges Z	3
Ramping angle $\alpha_{\text{max}}$	1.8 degrees
Circular interpolation milling a <sub>p</sub>	1 mm
Ramping length L for $\alpha_{\text{max}}$	286.4 mm
Circular interpolation milling $\emptyset$ $D_{min}$	61.4 mm
Circular interpolation milling $\emptyset$ $D_{max}$	78.5 mm
Series	Softcut®
Shank type	with bore
Setting angle κ	90 degrees
Milling application	Corner milling
Milling application	Circular milling
Milling application	Ramping
Spacing of the cutters	unequal spacing
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard
Type of product	Indexable insert cutter

## **Accessories**

Torque screwdriver, fixed setting set torque 3,8 Nm	211750 3,8
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP	674252 15IP

## Data sheet

# **⚠** Hoffmann Group

Set of insert screws 10-piece

219808