

Softcut® 90° indexable milling cutter MTC, with bore, Ø D / Zeff: 50/4 mm



Order data

Order number	215161 50/4
GTIN	4045197455215
Item class	210

Description

Version:

High precision square shoulder milling cutter with irregular pitch for very smooth cutting, very high precision and cutting power. High performance indexable square shoulder milling cutter with special geometry for reduced cutting forces for MTC applications under unstable conditions or for spindles with low drive power.

Application:

For corner milling to large depths, also slotting. General use in all steels including stainless steels. Especially for **MTC** (**Multi Task Cutting**) use on the new generation of turning / milling centres (**MTM**).

Note:

Use GARANT torque screwdriver TQ No. 211750 size 3.8 with bit No. 674252 size 15IP.

The insert pocket must be modified when using indexable inserts with a radius greater than 3.1 mm.

Number of effective inserts Z_{eff} : 4 Number of indexable inserts: 8

maximum cutting depth ap max: 28 mm

Overall length L_{tot}: 50 mm Mounting bore Ø: 22 mm

Pack of insert screws: 219808 (15IP; 3.8 Nm)

Technical description

maximum cutting depth apmax	28 mm
suitable indexable insert	AP 1805
Cutting edge \varnothing D_c	50 mm
Overall length L _{tot}	50 mm
Mounting bore \varnothing	22 mm
Pack of insert screws	219808 (15IP; 3.8 Nm)
Number of effective inserts $Z_{\mbox{\tiny eff}}$	4
Number of indexable inserts	8
Shank type	with bore
Setting angle κ	90 degrees
Milling application	Corner milling
Milling application	Ramping
Milling application	Circular milling
Spacing of the cutters	unequal spacing
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard

Accessories

Set of insert screws 10-piece	219808
Torque screwdriver, fixed setting set torque 3,8 Nm	211750 3,8
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 15IP	674252 15IP