

# Softcut® 90° shoulder mill, with bore, Ø D / Zeff: 50/4 mm



## **Order data**

Order number	215579 50/4
GTIN	4045197455338
Item class	210

## **Description**

#### **Version:**

High precision indexable face mill with irregular pitch for very smooth cutting, very high precision, and very high metal removal rate. **New generation** of high performance indexable face mills with special geometry for reduced cutting forces for MTC applications under unstable conditions or for spindles with low drive power.

### **Application:**

For face milling to large depths, also slotting. General use in all steels including stainless steels.

## **Spare part:**

Pack of insert screws No. 219826 (8IP; 2.2 Nm).

#### Note:

The insert seat must be modified when using indexable inserts with a radius greater than 2 mm. GARANT torque screwdriver TQ No. **211750 size 2.2**, use bit No. **674252 size 8IP**.

## Not for ramping or circular plunging!

The insert pocket must be modified when using indexable inserts with a radius greater than 2 mm.

Tool exchange: PowerCard Number of effective inserts Z<sub>eff</sub>: 4 Number of indexable inserts: 16

maximum cutting depth a<sub>p max</sub>: 39.5 mm

Overall length L<sub>tot</sub>: 55 mm Mounting bore Ø: 22 mm

Pack of insert screws: 219826 (8IP; 2.2 Nm)

# **Technical description**

Mounting bore Ø	22 mm
Overall length L <sub>tot</sub>	55 mm
suitable indexable insert	AP 1335
Pack of insert screws	219826 (8IP; 2.2 Nm)
maximum cutting depth a <sub>p max</sub>	39.5 mm
Cutting edge $\varnothing$ $D_c$	50 mm
Number of effective inserts $Z_{\mbox{\scriptsize eff}}$	4
Number of indexable inserts	16
Shank type	with bore
Setting angle κ	90 degrees
Milling application	End milling
Spacing of the cutters	unequal spacing
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard

# **Accessories**

Torque screwdriver, fixed setting set torque 2,2 Nm	211750 2,2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP	674252 8IP
Set of insert screws 10-piece	219826