

Garant
Shoulder mill 90°, with threaded shank, Ø D / number of teeth Z: 16/2 mm

Order data

Order number	215870 16/2
GTIN	4045197193032
Item class	210

Description
Application:

General application in all materials and for slot milling.

Note:

Arbors for milling cutters with thread see catalogue section 3.

Use GARANT torque screwdriver TQ No. **211750 size 1.2** with bit No. **674252 size 8IP**.

Overall length L_{tot} : 23 mm

Ø D_1 h6: 8.5 mm

Ø D_2 : 12.7 mm

Mounting thread M: M8

suitable indexable insert: AP.. 1003

Pack of insert screws: 219814 (8IP; 1.2 Nm)

Technical description

Ø D_1 h6	8.5 mm
suitable indexable insert	AP.. 1003
Ø D_2	12.7 mm
Mounting thread M	M8
Overall length L_{tot}	23 mm
Cutting edge Ø D_c	16 mm
Pack of insert screws	219814 (8IP; 1.2 Nm)

Number of cutting edges Z	2
Shank type	with threaded shank
Setting angle κ	90 degrees
Milling application	Circular milling
Milling application	Ramping
Milling application	End milling
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard
Type of product	Indexable insert cutter

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP	674252 8IP
Torque screwdriver, fixed setting set torque 1,2 Nm	211750 1,2
Set of insert screws 10-piece	219814