

Garant
Shoulder mill 90°, with threaded shank, Ø D / number of teeth Z: 24,7/4 mm


Order data

Order number	215870 24,7/4
GTIN	4045197193063
Item class	210

Description

Application:

General application in all materials and for slot milling.

Note:

Arbors for milling cutters with thread see catalogue section 3.

Use GARANT torque screwdriver TQ No. **211750 size 1.2** with bit No. **674252 size 8IP**.

Overall length L_{tot} : 35 mm

Ø D_1 h6: 12.5 mm

Ø D_2 : 20.7 mm

Mounting thread M: M12

suitable indexable insert: AP.. 1003

Pack of insert screws: 219814 (8IP; 1.2 Nm)

Technical description

Cutting edge Ø D_c	24.7 mm
Overall length L_{tot}	35 mm
suitable indexable insert	AP.. 1003
Mounting thread M	M12
Pack of insert screws	219814 (8IP; 1.2 Nm)
Ø D_2	20.7 mm
Ø D_1 h6	12.5 mm

Number of cutting edges Z	4
Shank type	with threaded shank
Setting angle κ	90 degrees
Milling application	Circular milling
Milling application	Ramping
Milling application	End milling
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard
Type of product	Indexable insert cutter

Accessories

Torque screwdriver, fixed setting set torque 1,2 Nm	211750 1,2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP	674252 8IP
Set of insert screws 10-piece	219814