

Garant
GARANT Power Tang 90° tangential high-performance shoulder mill, Weldon shank, Ø D / Z_{eff}: 25/2 mm

Order data

Order number	215972 25/2
GTIN	4045197940070
Item class	210

Description

GARANT Power Tang 90° tangential high-performance shoulder mill 25/2 mm
 Number of effective inserts Z_{eff} : 2
 Number of indexable inserts: 10
 maximum cutting depth $a_{p\text{max}}$: 39 mm
 Overhang L_1 : 54 mm
 Overall length L_{tot} : 112 mm
 Shank Ø D_s h6: 25 mm

Technical description

Number of effective inserts Z_{eff}	2
Overall length L_{tot}	112 mm
suitable indexable insert	LO.U
Shank Ø D_s h6	25 mm
Overhang L_1	54 mm
Cutting edge Ø D_c	25 mm
maximum cutting depth $a_{p\text{max}}$	39 mm
Pack of insert screws	219868 2 (8IP; 1.2 Nm)
Number of indexable inserts	10
Shank type	Weldon shank

Setting angle κ	90 degrees
Milling application	Corner milling
Spacing of the cutters	unequal spacing
Through-coolant	yes
Tool exchange	PowerCard

Accessories

Torque screwdriver, fixed setting set torque 1,2 Nm	211750 1,2
PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP	674252 8IP