

Garant
GARANT Power Tang 90° tangential high-performance shoulder mill, Weldon shank, Ø D / Z_{eff}: 40/4 mm

Order data

Order number	215972 40/4
GTIN	4045197940094
Item class	210

Description

GARANT Power Tang 90° tangential high-performance shoulder mill 40/4 mm
 Number of effective inserts Z_{eff} : 4
 Number of indexable inserts: 24
 maximum cutting depth $a_{p\text{max}}$: 47 mm
 Overhang L_1 : 69 mm
 Overall length L_{tot} : 131 mm
 Shank $\varnothing D_s$ h6: 32 mm

Technical description

maximum cutting depth $a_{p\text{max}}$	47 mm
Number of effective inserts Z_{eff}	4
Overall length L_{tot}	131 mm
Shank $\varnothing D_s$ h6	32 mm
Overhang L_1	69 mm
Pack of insert screws	219868 2 (8IP; 1.2 Nm)
Cutting edge $\varnothing D_c$	40 mm
suitable indexable insert	LO.U
Number of indexable inserts	24

Shank type	Weldon shank
Setting angle κ	90 degrees
Milling application	Corner milling
Spacing of the cutters	unequal spacing
Through-coolant	yes
Tool exchange	PowerCard

Accessories

PrecisionBit for Torx Plus®, shank E 6.3 Torx Plus® profile 8IP	674252 8IP
Torque screwdriver, fixed setting set torque 1,2 Nm	211750 1,2