### Garant

# Side / parting off milling cutter with plain shank HSS width ap = 1.5 mm, $\emptyset$ D / number of teeth Z: 50/4 mm



#### Order data

Order number	218408 50/4
GTIN	4045197533364
Item class	21P

#### Description

#### Version:

High-performance parting-off milling cutter system with choice of either collar and **low-cost** steel blade or collar and high-precision temperature-resistant HSS blade.

#### **Application:**

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

#### Use of the advertising text:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Order number: 218440 to 218444 (see main catalogue)

#### Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

#### Note:

Side and parting-off milling cutters available up to  $\emptyset$  D = 200 mm.

Through-coolant: no

maximum cutting depth  $a_{e max}$ : 12.75 mm Collar Ø d<sub>1</sub>: 24.5 mm

Collar length  $L_1$ : 36 mm

Overall length  $L_{tot}$  for  $a_p$  1.5 mm: 94.9 mm

Overall length  $L_{tot}$  for  $a_p$  2.2 mm: 95.5 mm

Shank Ø D, h6: 25 mm

## **Technical description**

Cutting edge $Ø D_c$	50 mm
Overall length $L_{tot}$ for $a_p$ 1.5 mm	94.9 mm
Overall length $L_{tot}$ for $a_p$ 2.2 mm	95.5 mm
Collar length L <sub>1</sub>	36 mm
Shank Ø D <sub>s</sub> h6	25 mm
Collar $\emptyset$ d <sub>1</sub>	24.5 mm
maximum cutting depth a <sub>e max</sub>	12.75 mm
suitable indexable insert	XC 1113
Number of cutting edges Z	4
Width a <sub>p</sub>	1.5 mm
Shank type	Plain shank
Tool material	HSS
Through-coolant	no
Type of product	Side milling cutter