Garant

Side / parting off milling cutter with collar HSS width ap = 1.5 mm, \emptyset D / number of teeth Z: 80/5 mm



Order data

Order number	218420 80/5
GTIN	4045197533692
Item class	21P

Description

Version:

High-performance parting-off milling cutter system with choice of either collar and **low-cost** steel blade or collar and **high-precision temperature-resistant HSS blade.**

Application:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Use of the advertising text:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Order number: 218440 to 218444 (see main catalogue)

Optional extras:

HSS spare blades can be reordered as accessories.

Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

Note:

HSS spare blades can be reordered as accessories.

Side and parting-off milling cutters available up to \emptyset D = 200 mm.

HSS spare blades can be ordered extra.

Note re advertising text:



HSS spare blades can be ordered as accessories (see main catalogue).

Through-coolant: no

Number of cutting edges Z: 5

maximum cutting depth a_{e max}: 20 mm

Collar Ø d₁: 40 mm

Base toolholder Ø d₂: 40 mm

 $\begin{array}{l} Overall \ length \ L_{tot} \ for \ a_p \ 1.5 \ mm; 51.4 \ mm \\ Overall \ length \ L_{tot} \ for \ a_p \ 2.2 \ mm; 52 \ mm \end{array}$

Technical description

Overall length L_{tot} for a_p 3.1 mm	52.8 mm
Overall length L _{tot} for a _p 1.5 mm	51.4 mm
maximum cutting depth a _{e max}	20 mm
Base toolholder Ø d ₂	40 mm
Mounting bore Ø	22 mm
Overall length L _{tot} for a _p 2.2 mm	52 mm
Collar Ø d₁	40 mm
suitable indexable insert	XC 1113
Cutting edge Ø D _c	80 mm
Number of cutting edges Z	5
Shank type	with bore
Tool material	HSS
Through-coolant	no
Type of product	Side milling cutter