Garant

Side / parting off milling cutter with collar HSS width ap = 2.2 mm, \varnothing D / number of teeth Z: 160/15 mm



Order data

Order number	218424 160/15
GTIN	4045197533920
Item class	21P

Description

Version:

High-performance parting-off milling cutter system with choice of either collar and **low-cost steel blade** or collar and **high-precision temperature-resistant HSS blade.**

Application:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Use of the advertising text:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Order number: 218440 to 218444 (see main catalogue)

Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

Note:

HSS spare blades can be ordered extra.

Side and parting-off milling cutters available up to \varnothing D = 200 mm.

Note re advertising text:

HSS spare blades can be ordered as accessories (see main catalogue).

Through-coolant: no

Number of cutting edges Z: 15

maximum cutting depth $a_{e\,max}$: 40 mm

Collar Ø d₁: 80 mm

Base toolholder Ø d₂: 80 mm

Overall length L_{tot} for a_p 2.2 mm: 65 mm Overall length L_{tot} for a_p 3.1 mm: 65.8 mm

Technical description

Base toolholder Ø d ₂	80 mm
Overall length L _{tot} for a _p 2.2 mm	65 mm
suitable indexable insert	XC 1119
Collar Ø d₁	80 mm
Overall length L _{tot} for a _p 3.1 mm	65.8 mm
Mounting bore Ø	40 mm
Cutting edge \varnothing D_c	160 mm
maximum cutting depth a _{e max}	40 mm
Number of cutting edges Z	15
Shank type	with bore
Tool material	HSS
Through-coolant	no
Type of product	Side milling cutter