

Garant

Side / parting off milling cutter with collar Steel width ap = 2.2 mm, Ø D / number of teeth Z: 125/10 mm

**Order data**

Order number	218426 125/10
GTIN	4045197533968
Item class	21P

Description**Version:**

High-performance parting-off milling cutter system with choice of either collar and **low-cost steel blade** or collar and **high-precision temperature-resistant HSS blade**.

Application:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Use of the advertising text:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Order number: 218440 to 218444 (see main catalogue)

Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

Note:

Side and parting-off milling cutters available up to Ø D = 200 mm.

HSS spare blades can be ordered extra.

Note re advertising text:

HSS spare blades can be ordered as accessories (see main catalogue).

Through-coolant: no

Number of cutting edges Z: 10
 maximum cutting depth $a_{e\max}$: 33.5 mm
 Collar $\varnothing d_1$: 58 mm
 Base toolholder $\varnothing d_2$: 58 mm
 Overall length L_{tot} for a_p 1.5 mm: 64.4 mm
 Overall length L_{tot} for a_p 2.2 mm: 65 mm

Technical description

Cutting edge $\varnothing D_c$	125 mm
Collar $\varnothing d_1$	58 mm
Base toolholder $\varnothing d_2$	58 mm
Mounting bore \varnothing	32 mm
Overall length L_{tot} for a_p 1.5 mm	64.4 mm
maximum cutting depth $a_{e\max}$	33.5 mm
suitable indexable insert	XC.. 1119
Overall length L_{tot} for a_p 3.1 mm	65.8 mm
Overall length L_{tot} for a_p 2.2 mm	65 mm
Number of cutting edges Z	10
Shank type	with bore
Through-coolant	no
Type of product	Side milling cutter