Garant

Side / parting off milling cutter with collar HSS width ap = 3.1 mm, \emptyset D / number of teeth Z: 100/8 mm



Order data

Order number	218428 100/8
GTIN	4045197534002
Item class	21P

Description

Version:

High-performance parting-off milling cutter system with choice of either collar and **low-cost** steel blade or collar and **high-precision temperature-resistant HSS blade.**

Application:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Use of the advertising text:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Order number: 218440 to 218444 (see main catalogue)

Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

Note:

HSS spare blades can be ordered extra.

Side and parting-off milling cutters available up to \varnothing D = 200 mm.

Note re advertising text:

HSS spare blades can be ordered as accessories (see main catalogue).

Through-coolant: no

Number of cutting edges Z: 8

maximum cutting depth $a_{e max}$: 26 mm Collar Ø d_1 : 48 mm Base toolholder Ø d_2 : 48 mm

Overall length L_{tot} for a_p 1.5 mm: 51.4 mm Overall length L_{tot} for a_p 2.2 mm: 52 mm

Technical description

Overall length L _{tot} for a _p 3.1 mm	52.8 mm
Overall length L _{tot} for a _p 1.5 mm	51.4 mm
Mounting bore Ø	27 mm
maximum cutting depth a _{e max}	26 mm
Collar Ø d₁	48 mm
Cutting edge \varnothing D_c	100 mm
suitable indexable insert	XC 1125
Overall length L _{tot} for a _p 2.2 mm	52 mm
Base toolholder Ø d ₂	48 mm
Number of cutting edges Z	8
Shank type	with bore
Tool material	HSS
Through-coolant	no
Type of product	Side milling cutter