## Garant

# Side / parting off milling cutter with collar HSS width ap = 3.1 mm, Ø D / number of teeth Z: 63/4 mm



## Order data

Order number	218428 63/4
GTIN	4045197533982
Item class	21P

## Description

#### Version:

High-performance parting-off milling cutter system with choice of either collar and **low-cost** steel blade or collar and high-precision temperature-resistant HSS blade.

#### **Application:**

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

#### Use of the advertising text:

For slitting and parting off milling. For high repetition accuracy in series production it is preferable to use the HSS blade.

Order number: 218440 to 218444 (see main catalogue)

#### Attention:

Please order the assembly key No. 279940 1 separately. See catalogue page 758.

#### Note:

HSS spare blades can be ordered extra.

Side and parting-off milling cutters available up to  $\emptyset$  D = 200 mm.

#### Note re advertising text:

HSS spare blades can be ordered as accessories (see main catalogue).

Through-coolant: no

Number of cutting edges Z: 4

maximum cutting depth  $a_{e max}$ : 15.5 mm Collar Ø d<sub>1</sub>: 32 mm Base toolholder Ø d<sub>2</sub>: 40 mm Collar length L<sub>1</sub>: 38 mm Overall length L<sub>tot</sub> for a<sub>p</sub> 1.5 mm: 51.4 mm

# **Technical description**

Mounting bore Ø	22 mm
Collar length L <sub>1</sub>	38 mm
Collar $\emptyset$ d <sub>1</sub>	32 mm
maximum cutting depth a <sub>e max</sub>	15.5 mm
Base toolholder Ø d <sub>2</sub>	40 mm
Overall length $L_{tot}$ for $a_p$ 1.5 mm	51.4 mm
Overall length $L_{tot}$ for $a_p$ 3.1 mm	52.8 mm
Overall length $L_{tot}$ for $a_p 2.2 \text{ mm}$	52 mm
suitable indexable insert	XC 1125
Cutting edge $Ø D_c$	63 mm
Number of cutting edges Z	4
Shank type	with bore
Tool material	HSS
Through-coolant	no
Type of product	Side milling cutter