



Shoulder mill 90° 5720VZ16, Plain shank, Ø D / number of teeth Z: 32/2 mm



Order data

Order number	220800 32/2
GTIN	2050002058248
Item class	28R

Description

Version:

Milling body with plain shank, balanced to $G = 6.3$ at 30,000 rpm. Shell-type milling cutters and milling cutters with modular interfaces have to be balanced together with their holder before use in high-speed copy milling. The design allows all radii of indexable inserts up to $r_e = 6.0$ mm to be mounted without modification to the milling head and without length correction.

Through-coolant: yes

maximum cutting depth $a_{p\max}$: 16 mm

Overhang L_1 : 75 mm

Overall length L_{tot} : 135 mm

Shank Ø D_s h6: 32 mm

suitable indexable insert: ZD.. 16M5

Insert screw: 229900 (TP20; 6.0 Nm)

Technical description

Cutting edge Ø D_c	32 mm
suitable indexable insert	ZD.. 16M5
Overhang L_1	75 mm
maximum cutting depth $a_{p\max}$	16 mm
Overall length L_{tot}	135 mm
Shank Ø D_s h6	32 mm
Insert screw	229900 (TP20; 6.0 Nm)
Number of cutting edges Z	2

Shank type	Plain shank
Setting angle κ	90 degrees
Milling application	End milling
Milling application	Ramping
Milling application	Circular milling
Through-coolant	yes
Type of product	Indexable insert cutter

Accessories

Clamping screw	229900
----------------	--------