



## High feed rate milling cutter 7792VX, with threaded shank, Ø D / number of teeth Z: 25/2 mm



### Order data

Order number	221905 25/2
GTIN	4059782503212
Item class	28R

### Description

#### Description:

The unique design of the indexable inserts together with their approach angle in the milling body greatly reduces the radial forces and diverts them into the axial direction. Particularly thick indexable inserts with 4 cutting edges for the heaviest duties and high cost-effectiveness. The tool has particular advantages for face milling and milling deep pockets. With its ground wiper chamfer it is equally well suited also to plunge milling and finish milling operations.

Machining strategy: HPC

Through-coolant: yes

Number of cutting edges Z: 2

maximum cutting depth  $a_{p,max}$ : 1.5 mm

Overall length  $L_{tot}$ : 35 mm

Mounting thread M: M12

suitable indexable insert: XD.. 0904

Indexable insert size: 09

### Technical description

maximum cutting depth $a_{p,max}$	1.5 mm
Overall length $L_{tot}$	35 mm
Indexable insert size	09
Cutting edge Ø $D_c$	25 mm
suitable indexable insert	XD.. 0904

Mounting thread M	M12
Insert screw	229917 (T15; 2.1 Nm)
Number of cutting edges Z	2
Through-coolant	yes
Shank type	with threaded shank
Milling application	Ramping
Milling application	Circular milling
Milling application	Plunging
Machining strategy	HPC

---

## Accessories

Clamping screw	229917
----------------	--------