



High feed rate milling cutter 7792VX, with threaded shank, Ø D / number of teeth Z: 32/2 mm



Order data

Order number	221905 32/2
GTIN	4059782504790
Item class	28R

Description

Description:

The unique design of the indexable inserts together with their approach angle in the milling body greatly reduces the radial forces and diverts them into the axial direction. Particularly thick indexable inserts with 4 cutting edges for the heaviest duties and high cost-effectiveness. The tool has particular advantages for face milling and milling deep pockets. With its ground wiper chamfer it is equally well suited also to plunge milling and finish milling operations.

Machining strategy: HPC

Through-coolant: yes

Number of cutting edges Z: 2

maximum cutting depth $a_{p,max}$: 2.5 mm

Overall length L_{tot} : 43 mm

Mounting thread M: M16

suitable indexable insert: XD.. 1205

Indexable insert size: 12

Technical description

Cutting edge Ø D_c	32 mm
Overall length L_{tot}	43 mm
Indexable insert size	12
suitable indexable insert	XD.. 1205
Insert screw	229908 (T15; 3.1 Nm)

maximum cutting depth $a_{p\max}$	2.5 mm
Mounting thread M	M16
Number of cutting edges Z	2
Through-coolant	yes
Shank type	with threaded shank
Milling application	Ramping
Milling application	Circular milling
Milling application	Plunging
Machining strategy	HPC

Accessories

Clamping screw	229908
----------------	--------