



## High feed rate milling cutter MFH Harrier, Plain shank, Ø D / number of teeth Z: 25/2 mm



### Order data

Order number	222050 25/2
GTIN	4960664707454
Item class	250

### Description

#### Description:

MFH Harrier high feed rate indexable face mills enable short machining times thanks to high feed rates and high cutting depths. The approach angle in combination with the convex cutting edges reduces the cutting forces and minimises the tendency to vibrate.

#### Application:

For increased productivity in face milling, pocket milling and slot milling. Because the cutting forces are so low, large overhangs for plunge milling pose no problem.

Machining strategy: HPC

Through-coolant: yes

Number of cutting edges Z: 2

maximum cutting depth  $a_{p\max}$ : 1.5 mm

maximum cutting depth  $a_{p\max}$  for LD geometry: 3.5 mm

Overhang  $L_1$ : 60 mm

Overall length  $L_{tot}$ : 140 mm

Shank Ø  $D_s$  h6: 25 mm

### Technical description

Number of cutting edges Z	2
Insert screw	229717 (15IP; 3.5 Nm)
Cutting edge Ø $D_c$	25 mm
Overhang $L_1$	60 mm
Shank Ø $D_s$ h6	25 mm

suitable indexable insert	SOMT..
Overall length $L_{tot}$	140 mm
Indexable insert size	10
maximum cutting depth $a_{p\ max}$	1.5 mm
maximum cutting depth $a_{p\ max}$ for LD geometry	3.5 mm
Through-coolant	yes
Shank type	Plain shank
Milling application	Plunging
Milling application	Circular milling
Milling application	Ramping
Machining strategy	HPC

---

## Accessories

Clamping screw	229717
----------------	--------