



## Indexable face mill 47.5° MFPN45, with bore, Ø D / number of teeth Z: 100/10 mm



### Order data

Order number	222800 100/10
GTIN	4960664602513
Item class	250

### Description

#### Version:

High performance face milling cutter with double-sided pentagonal indexable inserts. The combination of approach angle, chip chamber design as well as the geometries and cutting angles of the indexable inserts ensure outstanding metal removal rates, chip clearance, working life, and low cutting forces, and hence high cost-effectiveness.

Machining strategy: HPC

maximum cutting depth  $a_{p\max}$ : 6 mm

maximum external  $\varnothing D_{\max}$ : 113 mm

Overall length  $L_{\text{tot}}$ : 50 mm

Mounting bore  $\varnothing$ : 32 mm

suitable indexable insert: PN.. 1205

Insert screw: 229701

### Technical description

maximum cutting depth $a_{p\max}$	6 mm
Insert screw	229701
Cutting edge $\varnothing D_c$	100 mm
suitable indexable insert	PN.. 1205

maximum external $\varnothing D_{\max}$	113 mm
Mounting bore $\varnothing$	32 mm
Overall length $L_{\text{tot}}$	50 mm
Number of cutting edges Z	10
Shank type	with bore
Setting angle $\kappa$	47.5 degrees
Through-coolant	no
Machining strategy	HPC
Type of product	Indexable insert cutter

---

## Accessories

Clamping screw	229701
----------------	--------